

DRILL (9/32" or "K") SCREW
PILOT HOLES IN RAIL AS
REQUIRED. USE HOLES IN
LOAD BAR AS TEMPLATE
FOR HOLE LOCATION.

REMOVE CONCRETE
ANCHOR(S) AS REQUIRED

THREAD FORMING
SCREWS TO SECURE
RAILS (4 PLACES)

LOAD BAR

FILLER FORMER

STANDARD FORMER

THREAD FORMING
SCREWS TO SECURE
LOAD BAR (2 PLACES)
CAN BE RETRACTED
OR REMOVED DURING
GRATE PLACEMENT

EXPLODED VIEW



LOCATE TEE AS
REQUIRED ALONG
RAIL. AVOID
REMOVABLE
LEG BRACKETS

**ASSEMBLED VIEW
(FORMERS REMOVED)**

ABT[®], INC.

P.O. BOX 837 / 259 MURDOCK ROAD
TROUTMAN, NC 28166
(704) 528-9806 (800) 438-6057
www.abtdrains.com

INSTALLATION DRAWING © 2015 ABT, Inc.

**TRENCH FORMER DETAIL
1802 - TOGGLE LOCK - TEE USING LOAD BAR**

FILE: **DET-TL-TEE-03**

PART: **DET-TL-TEE**

Proprietary rights of ABT, Inc. are included in the information disclosed herein. The recipient, by accepting this document, agrees that neither this document nor the information disclosed herein nor any part thereof shall be copied, reproduced or transferred to others for manufacturing or for any other purpose except as specifically authorized in writing by ABT, Inc.

DISCLAIMER: The customer and the customer's architects, engineers, consultants and other professionals are completely responsible for the selection, installation, and maintenance of any product purchased from ABT, and EXCEPT AS EXPRESSLY PROVIDED IN ABT'S STANDARD WARRANTIES, ABT MAKES NO WARRANTY, EXPRESS OR IMPLIED, AS TO THE SUITABILITY, DESIGN, MERCHANTABILITY, OR FITNESS OF THE PRODUCT FOR THE CUSTOMER'S APPLICATION. Copies of ABT's standard warranties are available upon request.