



Treatment Train

- ① Surface Runoff
- ② Natural Infiltration
- ③ Bio-Remediation / Evapotranspiration
- ④ Vertical Bypass Pipe
- ⑤ Permavoid 85 Water Attenuation / Storage Units
- ⑥ Permavoid Wicking Cones for Passive Irrigation
- ⑦ Wicking Geotextile for Passive Irrigation
- ⑧ Permavoid 150 Water Attenuation / Storage Units
- ⑨ Controlled Discharge Outlet Pipe

Notes & Features

- Ⓐ Asphalt Pavement
- Ⓑ Compacted Subbase
- Ⓒ Emergency Surface Water Storage
- Ⓓ Geotextile or Geomembrane
- Ⓔ Geotextile (Mirafi 1100N)
- Ⓕ Runoff Scour Prevention



<p>ABT, INC. POLYDRAIN® TRENCH FORMER P.O. BOX 837, 259 MURDOCK ROAD TROUTMAN, NC 28166 www.abttrains.com (704) 528-9806</p>	TITLE: BS-PV85-PI-PV150 Bioswale Inlet - Passive Irrigation	
	DRAWN BY: S.M.W. SCALE: Graphical	CHECKED BY: XXX DATE: 08/20/15
<small>DISCLAIMER: The customer and the customer's architects, engineers, consultants and other professionals are completely responsible for the selection, installation, and maintenance of any product purchased from ABT, and EXCEPT AS EXPRESSLY PROVIDED IN ABT'S STANDARD WARRANTIES, ABT MAKES NO WARRANTY, EXPRESS OR IMPLIED, AS TO THE SUITABILITY, DESIGN, MERCHANTABILITY, OR FITNESS OF THE PRODUCT FOR CUSTOMER'S APPLICATION. Copies of ABT's standard warranties are available upon request.</small>		
<small>Proprietary right of ABT, Inc. are included in the information disclosed herein. The recipient, by accepting this document, agrees that neither this document nor the information disclosed herein nor any part thereof shall be copied, reproduced or transferred to others for manufacturing or for any other purpose except as specifically authorized in writing by ABT, Inc..</small>		